



DryLite® Dryers

Boost customer satisfaction with clean, dry cars and a better experience.

Belanger's DryLite® dryers connect with passing drivers by lighting up the exit area of your in-bay automatic. Attract attention from the street 24/7 to actively market your business and capture new customers.

Once drivers pull up to your wash entrance, LED-illuminated DryLite dryers assist with driver navigation to get them into position quickly with prompts to pull forward, stop, or back up, if necessary. This helps increase vehicle processing and throughput, which means more cars washed per day.

DryLite ups the experience factor for operators, too, with better performance, ease of maintenance, safety, and effectiveness. You choose how many nozzles you need to satisfy your drying requirements. And, you decide what position and angle of attack works best for each nozzle. Make easy adjustments by loosening and tightening a few bolts. Less maintenance time means more uptime for your dryers—and more happy, loyal customers.

Clean, dry cars and an end-to-end light show help make your car wash visibly better for you and your customers – and a visibly better car wash makes a better business.



SPECIFICATIONS

Physical Configurations:

3-Nozzle/30 HP -

One DryLite® AirCannon dryer centered on the Head Beam and one DryLite® AirCannon dryer on each Leg Assembly.

Tunnel Space Required	5'	or with silencers 6'	208V	90 FLA
Unit Height	11'	with silencers 11'	230V	84 FLA
Unit Width	13' 8"	with silencers 13' 8"	460V	42 FLA
Vehicle Height Clearance	7' 5"	approximately		

4-Nozzle/40 HP -

Two DryLite® AirCannon dryers centered on the Head Beam and one DryLite® AirCannon dryer on each Leg Assembly.

Tunnel Space Required	5'	or with silencers 6'	208V	120 FLA
Unit Height	11'	with silencers 11'	230V	112 FLA
Unit Width	13' 8"	with silencers 13' 8"	460V	56 FLA
Vehicle Height Clearance	7' 5"	approximately		

4-Nozzle/40 HP -

Two DryLite® AirCannon dryers centered on the Head Beam and one DryLite® SideKick™ dryer on each Leg Assembly.

Tunnel Space Required	5'	or with silencers 6'	208V	120 FLA
Unit Height	11'	with silencers 11'	230V	112 FLA
Unit Width	13' 8"	with silencers 13' 8"	460V	56 FLA
Vehicle Height Clearance	7' 5"	approximately		

5-Nozzle/50 HP -

Three DryLite® AirCannon dryers centered on the Head Beam and one DryLite® SideKick™ dryer on each Leg Assembly.

Tunnel Space Required	5'	or with silencers 6'	208V	150 FLA
Unit Height	11'	with silencers 11'	230V	140 FLA
Unit Width	13' 8"	with silencers 13' 8"	460V	70 FLA
Vehicle Height Clearance	7' 5"	approximately		



- 3-Nozzle/30 HP and 4-Nozzle/40 HP dryers are available in floor mount and wall mount frame designs.
- Many additional dryer configurations available.
- AirCannon® and SideKick™ dryers are also available without lights and come in multiple solid color options to match your brand.

Belanger
1001 Doheny Court
P.O. Box 5470
Northville, MI 48167-5470 USA
belangerinc.com | 248-349-7010

Utility Requirements:

BELANGER 

PART OF
OPW 
VEHICLE WASH
SOLUTIONS
a  DOVER company