



QuickFire®

At 200+ vehicles per hour, Belanger's QuickFire® is the most powerful front, side, and rear vehicle washer on the market. With revolutionary features such as the patented Caterpillar Bearings and Dual Directional Travel action, this wrap accurately senses different vehicle widths for increased surface contact and outstanding wash results.

What's more, the QuickFire® accommodates every vehicle with its patented oversized socket joint, which is Built-To-Tilt™ through a full 360 degrees, helping provide gentle yet thorough cleaning of vehicle front, side and back contours. QuickFire® is the only wrap that follows the car for extended cleaning, even at high line speeds. Customers love the show, and appreciate the results as QuickFire chases each car, and chases dirt off of even 'hard to clean' vehicle rears.

The bottom line? The QuickFire® enables tunnel operators to process vehicles at higher line speeds without sacrificing wash quality. With the patented Dyna Trigger™, the QuickFire® "fires" across the back of the vehicle for overlapping 'taillight-to-taillight' wash coverage, effectively eliminating rear skunk striping - no manual prepping required!



Custom Cleans Every Vehicle, Every Time
DynaTrigger™ senses & adjusts to vehicle widths

Washes 200+ CPH, With Highest Wash Quality
Industry's only 'following' wrap delivers extended rear cleaning at every line speed

Overlapping Cleaning Coverage, Front & Rear
Eliminates 'skunk striping' with extended boom length



Unsurpassed Contact To Clean Vertical Surfaces
With dual-directional drive for superior vehicle cleaning

Minimizes Potential For Damage To Vehicles
With dampening 360° pivot & oversized socket joint

Smooth Wheel Travel Throughout The Wash
With patented, grease-free 'caterpillar bearing' design

REQUIREMENTS

Physical Examples

Tunnel Space Required	10' 2 1/2"
Unit Height	10' 1"
Unit Width	12' 9"

Utility Examples

Electric Drive Option:

Electrical Requirements	(2) outputs from Controller @ 120 VAC (for Extend & Retract)
	(2) 1HP, 3-Phase, 208/240/460 VAC
Pneumatic Requirements	1 CFM @ 90-PSI minimum 120-PSI maximum
Water Requirements	(2) 3/4" Hoses @ 8 GPM @ 40 PSI

Hydraulic Drive Option:

Hydraulic Requirements	Same requirements as above plus - 6 GPM @ 900 PS
------------------------	---

Belanger
1001 Doheny Court
P.O. Box 5470
Northville, MI 48167-5470 USA
belangerinc.com | 248-349-7010

©2020 Belanger Inc. Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation. Prices subject to change without notice.

COLOR OPTIONS

Choose from two vivid Neo-Tex™ wash colors



BELANGER

PART OF
OPW
VEHICLE WASH SOLUTIONS
a DOVER company