




Undercarriage Manifold

Increase your wash package revenue with the Undercarriage Manifold. The Undercarriage Manifold effectively flushes away undercarriage grime to help protect the critical underbody areas of each vehicle. This powerful, floor-mounted manifold is manufactured with two rows of five flat jet nozzles, each uniquely positioned at opposite 45-degree angles from the centerline. This innovative angled nozzle delivery provides superior cleaning into even the hardest-to-reach areas of any vehicle's undercarriage. The Undercarriage Manifold is constructed with a top-quality aluminum which is then e-coated for ultimate corrosion protection.

With Belanger's Undercarriage Manifold, operators will experience trouble-free performance and outstanding undercarriage wash results.

Drive your wash package revenue with the optional Undercarriage Manifold w/Rust Inhibitor. This option consists of the Undercarriage Manifold with an Automatic Fluid Injection System (AFIS) added on for use as a rust inhibitor. This AFIS effectively delivers your rust inhibitor chemical of choice through the Undercarriage Manifold's delivery nozzles for even application protection.



Undercarriage Manifold

Effectively Flush Away Undercarriage Soils

2 rows of 5 flat jet nozzles, positioned at opposing 45° angles provide superior cleaning into even the hardest-to-reach areas of the undercarriage

Increase Wash Package Revenue

Offer the underbody wash service that's important to customers - and add an Automatic Fluid Injection System for Rust Inhibitors to make even more money

Requires "Zero" Tunnel Space

Quickly incorporates into any wash configuration



Easy Installation

Floor-mounted design which can be quickly installed under other tunnel equipment to easily accommodate every site's needs

Extreme Durability

E-coated aluminum construction will never corrode and is a cost-effective, long-term upgrade to any tunnel

Maintenance-Free Design

Durable zero-moving-parts design delivers maximum service life and zero maintenance requirements

REQUIREMENTS

Physical Examples

Unit Height	2"
Unit Length	3' 10" (*May be installed on compatible pieces of wash equipment)

Utility Examples

Water Requirements	3/4" water feed
--------------------	-----------------

Belanger
1001 Doheny Court
P.O. Box 5470
Northville, MI 48167-5470 USA
belangerinc.com | 248-349-7010

BELANGER 

PART OF
OPW 
VEHICLE WASH SOLUTIONS
a **DOVER** company